



US007649744B2

(12) **United States Patent**
Zadesky et al.

(10) **Patent No.:** **US 7,649,744 B2**
(45) **Date of Patent:** **Jan. 19, 2010**

(54) **HANDHELD COMPUTING DEVICE**

(75) Inventors: **Stephen Paul Zadesky**, Portola Valley, CA (US); **Stephen Brian Lynch**, Portola Valley, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/395,570**

(22) Filed: **Feb. 27, 2009**

(65) **Prior Publication Data**

US 2009/0164035 A1 Jun. 25, 2009

Related U.S. Application Data

(62) Division of application No. 10/884,172, filed on Jul. 2, 2004, now Pat. No. 7,515,431.

(51) **Int. Cl.**
H05K 5/00 (2006.01)

(52) **U.S. Cl.** **361/752**; 174/50.51; 174/50; 174/54

(58) **Field of Classification Search** 361/728, 361/752, 793, 794; 174/50.51, 50, 54
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D264,969 S	6/1982	McGourty	
4,976,435 A	12/1990	Shatford et al.	
5,192,082 A	3/1993	Inoue et al.	
5,661,632 A	8/1997	Register	
5,917,545 A	6/1999	Kowno et al.	
D412,940 S	8/1999	Kato et al.	
5,964,661 A	10/1999	Dodge	
6,058,356 A *	5/2000	Swanson et al.	702/99
D430,169 S	8/2000	Scibora	
6,122,526 A	9/2000	Parulski et al.	
D432,523 S	10/2000	Grinkus et al.	

6,127,986 A	10/2000	Wen et al.
D437,860 S	2/2001	Suzuki et al.
6,220,680 B1	4/2001	Chen
6,227,966 B1	5/2001	Yokoi

(Continued)

OTHER PUBLICATIONS

"Maxtor OneTouch II FireWire and USB", Maxtor.com, <http://www.maxtor.com/portal/site/Maxtor/menuitem.ba88f6d7cf664718376049b2913460> . . . downloaded Dec. 1, 2004.

(Continued)

Primary Examiner—Dean A. Reichard


Assistant Examiner—Abiy Getachew

(74) *Attorney, Agent, or Firm*—Beyer Law Group LLP

(57) **ABSTRACT**


A handheld computing device and handheld music player are disclosed. The handheld computing device includes a seamless enclosure formed from an extruded tube. The extruded tube includes open ends and internal rails which serve as a guide for slidably assembling an operational assembly through the open ends of the extruded tube, a reference surface for positioning the operational assembly relative to an access opening in the seamless enclosure, and a support structure for supporting the operational assembly during use. The handheld music player includes an elongated extruded tube extending along a longitudinal axis. The elongated extruded tube has a first open end and a second open end opposite the first open end, and defines an internal lumen which is sized and dimensioned for slidable receipt of operational components of the handheld music player. The lumen includes rails for guiding the operational components to their desired position within the lumen.

20 Claims, 11 Drawing Sheets



U.S. PATENT DOCUMENTS

6,249,427 B1	6/2001	Carroll	7,397,003 B2 *	7/2008	Cox et al.	177/238
6,254,477 B1	7/2001	Sasaki et al.	7,495,659 B2	2/2009	Marriott et al.	
6,262,785 B1	7/2001	Kim	7,515,431 B1 *	4/2009	Zadesky et al.	361/752
6,292,556 B1	9/2001	Laetsch	2001/0034222 A1	10/2001	Roustaei et al.	
D448,810 S	10/2001	Goto	2002/0195562 A1	12/2002	Salapow et al.	
D450,713 S	11/2001	Masamitsu et al.	2003/0100275 A1	5/2003	Hsu et al.	
6,314,483 B1	11/2001	Goto et al.	2004/0053014 A1	3/2004	Sato	
6,319,631 B1	11/2001	Bay et al.	2004/0224638 A1	11/2004	Fadell et al.	
D452,250 S	12/2001	Chan	2005/0052425 A1	3/2005	Zadesky et al.	
D455,793 S	4/2002	Lin	OTHER PUBLICATIONS			
6,449,164 B1 *	9/2002	Gershfeld	"Maxtor OneTouch USB OneTouch Family", Maxtor.com, http://www.maxtor.com/portal/site/Maxtor/menuitem.ba88f6d7cf664718376049b2913460... downloaded Dec. 1, 2004.			
D468,365 S	1/2003	Bransky et al.	CoolerMaster Wave Master Black Aluminum Case Review:, PCStats.com, http://www.pcstats.com/articleview.cfm?articleID=1552 , Dowloaded Dec. 1, 2004.			
D469,109 S	1/2003	Andre et al.	Office Action mailed Nov. 16, 2005 from U.S. Appl. No. 10/884,172.			
D472,245 S	3/2003	Andre et al.	Final Office Action mailed May 4, 2006 from U.S. Appl. No. 10/884,172.			
6,643,918 B2	11/2003	Ortiz et al.	Office Action mailed Jul. 27, 2007 from U.S. Appl. No. 10/884,172.			
D483,809 S	12/2003	Lim	Final Office Action mailed Dec. 28, 2007 from U.S. Appl. No. 10/884,172.			
D489,731 S	5/2004	Huang	Office Action mailed Aug. 6, 2008 from U.S. Appl. No. 10/884,172.			
D490,068 S	5/2004	Chen	Notice of Allowance mailed Dec. 1, 2008 from U.S. Appl. No. 10/884,172.			
6,790,556 B1	9/2004	Meitav et al.	Supplemental Notice of Allowability mailed Feb. 4, 2009 from U.S. Appl. No. 10/884,172.			
6,795,715 B1	9/2004	Kubo et al.	U.S. Appl. No. 29/196,832, filed Jan. 5, 2004.			
D497,618 S	10/2004	Andre et al.	* cited by examiner			
6,837,435 B2	1/2005	Kehoe et al.				
6,840,311 B2	1/2005	Ghosh et al.				
D506,476 S	6/2005	Andre et al.				
D515,545 S	2/2006	Griffin				
D516,579 S	3/2006	Nakamura				
7,013,164 B2	3/2006	Lin				
D521,023 S	5/2006	Kim et al.				
7,046,230 B2	5/2006	Zadesky et al.				
7,070,881 B2	7/2006	Kishiyama et al.				







FIG. 2






FIG. 4







FIG. 5






FIG. 7B







FIG. 7A






FIG. 9A




FIG. 9B




FIG. 9D









FIG. 9C





1

HANDHELD COMPUTING DEVICE**CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a Divisional of, and claims the benefit of priority under 35 U.S.C. § 120 to, application Ser. No. 10/884, 172, filed on Jul. 2, 2004 and entitled "HANDHELD COMPUTING DEVICE" which is hereby incorporated herein by reference.

This application is also related to the following U.S. Patent Applications, which are hereby incorporated herein by reference: application Ser. No. 29/196,832, filed on Jan. 5, 2004 and entitled "MEDIA DEVICE," now abandoned; application Ser. No. 10/643,256, filed on Aug. 18, 2003 and entitled "MOVABLE TOUCHPAD WITH ADDED FUNCTIONALITY," now U.S. Publication No. 2005-0052425; application Ser. No. 10/188,182, filed on Jul. 1, 2002 and entitled "TOUCHPAD FOR HANDHELD DEVICE," now U.S. Pat. No. 7,046,230, issued on May 16, 2006; application Ser. No. 10/722,948, filed on Nov. 25, 2003 and entitled "TOUCHPAD FOR HANDHELD DEVICE," now U.S. Pat. No. 7,495,659, issued on Feb. 24, 2009 and application Ser. No. 10/423,490, filed on Apr. 25, 2003 and entitled "MEDIA PLAYER SYSTEM," now U.S. Publication No. 2004-0224638.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates generally to portable computing devices. More particularly, the present invention relates to enclosures of portable computing devices and methods of assembling portable computing devices.

2. Description of the Related Art

In recent years, portable computing devices such as laptops, PDAs, media players, cellular phones, etc., have become small, light and powerful. One factor contributing to this phenomena is in the manufacturer's ability to fabricate various components of these devices in smaller and smaller sizes while in most cases increasing the power and or operating speed of such components. Unfortunately, the trend of smaller, lighter and powerful presents a continuing design challenge in the design of some components of the portable computing devices.

One design challenge associated with the portable computing devices is the design of the enclosures used to house the various internal components of the portable computing devices. This design challenge generally arises from two conflicting design goals—the desirability of making the enclosure lighter and thinner, and the desirability of making the enclosure stronger and more rigid. The lighter enclosures, which typically use thinner plastic structures and fewer fasteners, tend to be more flexible and therefore they have a greater propensity to buckle and bow when used while the stronger and more rigid enclosures, which typically use thicker plastic structures and more fasteners, tend to be thicker and carry more weight. Unfortunately, increased weight may lead to user dissatisfaction, and bowing may damage the internal parts of the portable computing devices.

Furthermore, in most portable computing devices, the enclosures are mechanical assemblies having multiple parts that are screwed, bolted, riveted, or otherwise fastened together at discrete points. For example, the enclosures typically have included an upper casing and a lower casing that are placed on top of one another and fastened together using screws. These techniques typically complicate the housing design and create aesthetic difficulties because of undesirable

2

cracks, seams, gaps or breaks at the mating surfaces and fasteners located along the surfaces of the housing. For example, a mating line surrounding the entire enclosure is produced when using an upper and lower casing. Not only that, but assembly is often a time consuming and cumbersome process. For example, the assembler has to spend a certain amount of time positioning the two parts and attaching each of the fasteners. Furthermore, assembly often requires the assembler to have special tools and some general technical skill.

Another design challenge is in techniques for mounting structures within the portable computing devices. Conventionally, the structures have been laid over one of the casings (upper or lower) and attached to one of the casings with fasteners such as screws, bolts, rivets, etc. That is, the structures are positioned in a sandwich like manner in layers over the casing and thereafter fastened to the casing. This methodology suffers from the same drawbacks as mentioned above, i.e., assembly is a time consuming and cumbersome.

In view of the foregoing, there is a need for improved enclosures for portable computing devices. Particularly, enclosures that are more cost effective, smaller, lighter, stronger and aesthetically more pleasing than current enclosure designs. In addition, there is a need for improvements in the manner in which structures are mounted within the enclosures. For example, improvements that enable structures to be quickly and easily installed within the enclosure, and that help position and support the structures in the enclosure.

SUMMARY OF THE INVENTION

The invention relates, in one embodiment, to a handheld computing device. The computing device includes a seamless enclosure formed from an extruded tube. The extruded tube includes open ends and internal rails which serve as a guide for slidably assembling a user interface assembly through the open ends of the extruded tube, a reference surface for positioning the user interface assembly relative to an access opening in the seamless enclosure, and a support structure for supporting the user interface assembly during use.

The invention relates, in another embodiment, to a method of assembling a handheld computing device. The method includes providing an enclosure formed from an extruded tube including open ends and internal rails. The method also includes providing operational components for performing operations associated with the handheld computing device. The method further includes inserting the operational components into the extruded tube through an open end of the extruded tube. The operational components slide along the internal rail during insertion. The internal rails also help to locate the operational components in their desired position within the extruded tube. The method additionally includes securing the operational components to the extruded tube.

The invention relates, in another embodiment, to a handheld music player. The hand held music player includes an elongated extruded tube extending along a longitudinal axis, and having a first open end and a second open end opposite the first open end. The elongated extruded tube defines an internal lumen which is sized and dimensioned for slidable receipt of operational components of the handheld music player. The lumen includes rails for guiding the operational components to their desired position within the lumen.

The invention relates, in another embodiment, to a handheld computing device. The handheld computing device includes a seamless enclosure having a substantially planar front surface. The planar front surface is configured to present a user interface sub system of the handheld device. The seam-

3

less enclosure is formed from an extruded tube having open ends and internal rails. The open ends is configured to receive the user interface sub system therethrough during assembly of the handheld device. The internal rails are configured to locate the user interface sub system in its desired position relative to the planar front surface of the enclosure during assembly of the handheld computing device.

The invention relates, in another embodiment, to a method of manufacturing a handheld computing device. The method includes forming an enclosure for the handheld device. The formation includes at least extruding a tube with a substantially planar surface and internal rails and cutting the tube to a desired length where the cutting operation produces openings at each end of the tube. The method also includes forming one or more holes in the substantially planar surface. The method further includes inserting a display assembly into the tube through one of the openings. The display assembly includes a substantially planar printed circuit board and a display. The printed circuit board slides along the internal rails during insertion. The internal rails locate the display behind a first hole and adjacent the planar surface of the tube. The method additionally includes inserting a planar input device into the tube through one of the openings. The planar input device slides along the internal rails during insertion. The internal rails locate the input device behind a second hole and adjacent the planar surface of the tube.

The invention relates, in another embodiment, to a planar retaining plate. The retaining plate includes a body. The retaining plate also includes a first set of flexure arms extending from a first side of the body and a second set of flexure arms extending from a second side of the body opposite the first side. Each of the flexure arms are configured for insertion into a different slot located on a device enclosure in order to secure the retaining plate to the device enclosure. The retaining plate serves as a reference surface to various components located internal or external to the device enclosure.

The invention relates, in another embodiment, to an interface assembly of a handheld computing device. The handheld computing device has an enclosure and a first electronic device contained therein. The interface assembly includes a printed circuit board (PCB) divided into a flexure portion, a first base portion and a second base portion. The flexure portion is positioned between the first and second base portions. The flexure portion allows the first base portion to move relative to the second base portion. The second base portion is attached to the first electronic device. The interface assembly also includes a second electronic device attached to the first base portion, and operatively coupled to the first electronic device. The interface assembly further includes a support plate attached to the second electronic device. The flexure portion is configured to flex so that the first base portion shifts relative to the second base portion thereby allowing the plate to be correctly aligned with the enclosure during assembly of the handheld computing device.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be readily understood by the following detailed description in conjunction with the accompanying drawings, wherein like reference numerals designate like structural elements, and in which:

FIG. 1 is an exploded perspective diagram of an electronic device, in accordance with one embodiment of the present invention.

FIG. 2 is a perspective diagram of a handheld computing device, in accordance with one embodiment of the present invention.

4

FIG. 3A is a diagram of an assembled hand held computing device, in accordance with one embodiment of the present invention.

FIG. 3B is a diagram of the hand held computing device of FIG. 3A in its unassembled form, in accordance with one embodiment of the present invention.

FIG. 4 is top view diagram, in cross section, of an assembled hand held computing device, in accordance with one embodiment of the present invention.

FIG. 5 is bottom view diagram, in cross section, of the assembled hand held computing device, in accordance with one embodiment of the present invention.

FIGS. 6A-6C show the insertion and mounting of an input assembly inside a seamless enclosure, in accordance with one embodiment of the present invention.

FIGS. 7A and 7B show a bottom plate in its unassembled and assembled positions, in accordance with one embodiment of the present invention.

FIGS. 8A-8C are diagrams illustrating the audio subassembly in accordance with one embodiment of the present invention.

FIG. 9A is a front perspective view of a seamless enclosure, in accordance with one embodiment of the present invention.

FIG. 9B is a rear perspective view of a seamless enclosure, in accordance with one embodiment of the present invention.

FIG. 9C is a front view of a seamless enclosure, in accordance with one embodiment of the present invention.

FIG. 9D is a rear view of a seamless enclosure, in accordance with one embodiment of the present invention.

FIG. 9E is a top view of a seamless enclosure, in accordance with one embodiment of the present invention.

FIG. 9F is a bottom view diagram of a seamless enclosure, in accordance with one embodiment of the present invention.

FIG. 9G is a right side view of a seamless enclosure, in accordance with one embodiment of the present invention.

FIG. 9H is a left side view of a seamless enclosure, in accordance with one embodiment of the present invention.

FIG. 10 is a method of manufacturing an electronic device, in accordance with one embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The invention generally pertains to portable computing devices and more particularly to components of and methods for assembling portable computing devices. One aspect of the invention relates to a seamless enclosure that includes open ends and internal rails which serve as a guide for slidably assembling the internal components of the portable computing devices through the open ends of the seamless enclosure, as well as positioning and supporting the internal components in their assembled position within the seamless enclosure. The seamless enclosure may for example be formed via an extrusion process. Another aspect of the invention relates to a planar retaining plate, which serves as a multi-positional reference surface to various components of the portable computing devices. The retaining plate may for example be assembled within the lumen of the seamless enclosure to provide a reference surface to internal and external parts of the portable computing device. Another aspect of the invention relates to assemblies capable of flexing in order to align interfacing parts. For example, aligning a plate within the lumen of the seamless enclosure. Yet another aspect of the invention relates to a method of manufacturing a portable computing device. The method may include extruding a tube with a substantially planar surface and internal rails, cutting the tube to a desired length, forming one or more access openings in the substantially planar surface, sliding the user

5

interface assembly along the internal rails into the tube, and thereafter locating and supporting the user interface assembly behind an access opening and adjacent the planar surface of the tube via the internal rails.

These and other embodiments of the invention are discussed below with reference to FIGS. 1-10. However, those skilled in the art will readily appreciate that the detailed description given herein with respect to these figures is for explanatory purposes as the invention extends beyond these limited embodiments.

FIG. 1 is an exploded perspective diagram of an electronic device 50, in accordance with one embodiment of the present invention. The device 50 may be sized for one-handed operation and placement into small areas such as a pocket, i.e., the device 50 can be a handheld pocket sized electronic device. By way of example, the electronic device 50 may correspond to a computer, media device, telecommunication device and/or the like.

The device 50 includes a housing 52 that encloses and supports internally various electrical components (including for example integrated circuit chips and other circuitry) to provide computing operations for the device 50. The housing 52 also defines the shape or form of the device 50. That is, the contour of the housing 52 may embody the outward physical appearance of the device 50. The housing 52 generally includes a main body 54 in the form of an integral tube. By integral, it is meant that the main body is a single complete unit. By being integrally formed, the main body has a substantially seamless appearance, which is unlike conventional housings, which include two parts that are fastened together thereby forming a seam therebetween. Because of the tube like configuration, the main body 54 defines a cavity 56 therethrough between a first open end 58 and second open end 60 located opposite the first open end 58. The main body 54 also includes one or more windows 62, which provide access to the electrical components, particularly the user interface elements, when they are assembled inside the cavity 56 of the main body 54.

In order to seal the main body 54, the housing 52 additionally includes a pair of end caps 64A and 64B. Each of the end caps 64 is configured to cover one of the open ends 58 or 60 thereby forming a fully enclosed housing system. The end caps 64 may be formed from similar or different materials as the main body 54. Furthermore, the end caps 64 may be attached to the main body 54 using a variety of techniques, including but not limited to, fasteners, glues, snaps, and/or the like. In some cases, the end caps 64 may be positioned on the surface of the open ends 58 and 60. If so, they typically have the same shape as the outer periphery of the main body 54. In order to eliminate gaps, cracks or breaks on the front and side surfaces, the end caps 64 may alternatively be placed inside the cavity 56 at each of the ends. In this arrangement, the outer periphery of the end cap 64 generally matches the inner periphery of the main body 54. This implementation is typically preferred in order to form a housing 52 with a uniform and seamless appearance, i.e., no breaks when looking directly at the front, back or side of the housing.

The cross sectional shape, including both the outer and inner shapes, of the main body 54 may be widely varied. They may be formed from simple or intricate shapes whether rectilinear and/or curvilinear. For hand held devices, it is typically preferred to use a shape that better fits the hand (e.g., form fits). By way of example, a rectangle with curved edges or an oval or pill shaped cross section having curvature that more easily receives the hand may be used. It should be noted that the inner cross sectional shape may be the same or different from the external cross sectional shape of the main

6

body. For example, it may be desirable to have a pill shaped external and a rectangularly shaped interior, etc. In addition, although not a requirement, the front surface of the main body 54 may be substantially planar for placement of the user interface of the device 50.

The device 50 also includes one or more electronic subassemblies 66. The subassemblies 66 each include a carrier 68 and one or more operational components 70 of the electronic device 50. The carrier 68 provides a structure for carrying the operational components 70 and supporting them when assembled inside the housing 52. By way of example, the carrier 68 may be formed from plastics, metals and/or a printed circuit board (PCB). The operational components 70, on the other hand, perform operations associated with the computing device 50. The operational components 70 may for example include user interface elements 70A and/or circuit elements 70B. The user interface elements 70A allow a user to interact with the computing device 50. By way of example, the user interface elements 70A may correspond to a display and/or an input device such as a keypad, touch pad, touch screen, joystick, trackball, buttons, switches and/or the like. The circuit components 70B, on the other hand, perform operations such as computing operations for the computing device 50. By way of example, the computing components 70B may include a microprocessor, memory, hard drive, battery, I/O connectors, switches, power connectors, and/or the like.

During assembly, the subassemblies 66 are positioned inside the cavity 56 of the main body 54. In particular, the subassemblies 66 are inserted into one of the open ends 58 or 60 of the main body 54 mainly along a longitudinal axis 74 of the main body 54 to their desired position within the housing 52. Once positioned inside the cavity 56, the end caps 64 of the housing 52 may be attached to the main body 54 in order to fully enclose the housing 52 around the subassemblies 66. In most cases, the user interface elements 70A are positioned relative to the window opening 62 so that a user may utilize the user interface elements 70A. By way of example, the window 62 may allow viewing access to a display or finger access to a touch pad or button.

In order to more efficiently assemble the electronic subassemblies 66 inside the cavity 56, the device 50 includes an internal rail system 78 disposed inside the cavity 56 of the main body 54. In most cases, the internal rail system 78 is integrally formed with the main body 54, i.e., formed as a single part. The internal rail system 78 is configured to receive the various subassemblies 66 and guide them to their desired position within the main body 54 when the subassemblies 66 are inserted through one of the open ends 58 or 60. The internal rail system 78 enables the subassemblies 66 to be easily and quickly assembled within the device 50. For example, the rail system 78 provides for insertion (or removal) with minimal effort and without tools. The internal rail system 78 also helps support and store the subassemblies 66 in an organized manner within the device 50. By way of example, the rail system 78 may store the subassemblies 66 in a stacked parallel arrangement thereby using available space more efficiently.

As shown, the rail system 78 includes at least one set of opposed rails 80, each of which extends longitudinally through the cavity 56 and each of which protrudes from the inner sides of the main body 54. The rails 80 are configured to receive the subassembly 66 and cooperate to guide subassemblies 66 to their desired position within the housing 52. The internal rails 80 generally allow the subassemblies 66 to be slid into the cavity 56 through the open ends 58 or 60 following the longitudinal axis 74 of the main body 54. That is, the

subassemblies 66 and more particularly the carrier 68 are capable of sliding in and out of the housing 52 along one or more surfaces of the rails 80.

The portion of the subassemblies 66 that engages the rails 80 may be a surface of the subassemblies or alternatively one or more posts or mounts that extend outwardly from the subassemblies 66. Furthermore, the reference surfaces for the opposed rails 80 may be positioned in the same plane or they may be positioned in different planes. The configuration generally depends on the configuration of the subassemblies 66. By way of example, in some cases, the subassemblies 66 may have a cross section that is stepped rather than completely planar. In cases such as these, the opposed rails 80 have reference surfaces in different planes in order to coincide with the stepped cross section. Moreover, although typically continuous between the ends, each of the rails 80 may be segmented or include removed portions as for example at the ends for placement of the flush mounted end caps.

The width of the rails 80 may be widely varied. For example, they may be one integral piece that extends entirely from one side to the other, or they may be separate pieces with a gap located therebetween (as shown). The position and cross sectional dimensions and shapes of each of the rails may also be widely varied. The size and shape as well as the position of the rails 80 generally depends on the configuration of the sub assemblies 66. The rails 80 may have the same shape and size or they may have different shape and size. In most cases, the size and shape is a balance between keeping them as small as possible (for weight and space requirements) while providing the required reference surface and ample support to the subassemblies 66.

To elaborate, the rails 80 define one or more channels 82 that receive the one or more subassemblies 66. In the illustrated embodiment, the rails 80 along with the main body 54 define a pair of channels, particularly an upper channel 82A and a lower channel 82B. The upper channel 82A receives a first subassembly 66A and the lower channel 82B receives a second subassembly 66B. It should be noted, however, that this is not a limitation and that additional sets of rails 80 may be used to produce additional channels 82. It should also be noted that although only one subassembly 66 is shown for each channel 82 this is not a requirement and that more than one subassembly 66 may be inserted into the same channel 82. Moreover, it should be noted that the subassemblies are not limited to being fully contained within a single channel and that portions of a sub assembly may be positioned in multiple channels. For example, the second subassembly 66B, which is positioned in the lower channel 82B, may include a protruding portion that is positioned through the rails 80 and into the upper channel 82A.

The channels 82 generally include an entry point and a final point. The entry point represents the area of the channel 82 that initially receives the subassemblies 66, i.e., the area proximate the ends of the main body 54. The final point, on the other hand represents the area of the channel 82 that prevents further sliding movement. The final point may for example set the final mount position of the sub assemblies 66 within the housing 52. The final point may for example correspond to an abutment stop. The abutment stop may be integral with the main body 54 or a separate component. By way of example, the abutment stop may correspond to one or more posts that are mounted inside the cavity 56 on the inside surface of the main body 54 at a predetermined distance along the longitudinal axis 74.

In order to prevent the subassemblies 66 from sliding once assembled, the interface between the subassemblies 66 and housing 52 may include a locking or securing mechanism.

The locking mechanism 86 generally consists of two parts, a housing side locking feature and a subassembly side locking feature that are cooperatively positioned so that when the subassembly 66 is inserted into the housing 52, the locking features engage with one another thus holding the subassembly 66 in its desired position within the housing 52. In most cases, the locking features are configured to provide quick and easy assembly of the subassembly into the housing without the use of tools. The locking features may correspond to snaps, friction couplings, detents, flexures and/or the like. Alternatively or additionally, the assemblies 66 may be attached to the main body 54 with fasteners or adhesives.

In the illustrated embodiment, the subassemblies 66 each include a flexure tab 88 that engages a recess 90 located on an inner surface of the main body 54. When the subassembly 66 is slid into the housing 52, the tab 88 snaps into the recess 90 thereby securing the subassembly 66 at a predetermined position along the longitudinal axis 74. That is, because the tabs 88 flex, they allow the subassemblies 66 to pass when pushed into the cavity 76. When the subassemblies 66 pass over the recess 90, the tabs 88 resume their natural position thereby trapping the subassemblies 66 in the channel 82 between the locking tab/recess 88/90 and the abutment stop at the end of the channel 82. Using this arrangement, the subassemblies 66 are prevented from sliding out of the channels 82 on their own. In order to remove the subassembly 66, a user simply lifts the tab 88 away from the recess 90 while pulling on the subassembly 66. The recess 90 and abutment stop may cooperate to set the final position of the subassembly 66 in the cavity 56 of the main body 54. For example, the recess and abutment stop may be configured to position the user interface elements 70A directly behind the window opening 62 so that a user has full access to the user interface elements 70A.

In accordance with one embodiment, the main body 54 including the internal rails 80 is formed via an extrusion process. The extrusion process is capable of producing an integral tube without seams, cracks, breaks, etc. As is generally well known, extrusion is a shaping process where a continuous work piece is produced by forcing molten or hot material through a shaped orifice, i.e., the extrusion process produces a length of a particular cross sectional shape. The cross sectional shape of the continuous or length of work piece is controlled at least in part on the shaped orifice. As the shaped work piece exits the orifice, it is cooled and thereafter cut to a desired length. As should be appreciated, the extrusion process is a continuous high volume process that produces intricate profiles and that accurately controls work piece dimensions (which can be a necessity for smaller parts). Furthermore, because extrusion has low tooling costs, it is relatively inexpensive when compared to other forming or manufacturing processes.

The main body 54 may be formed from a variety of extrudable materials or material combinations including but not limited to metals, metal alloys, plastics, ceramics and/or the like. By way of example, the metals may correspond to aluminum, titanium, steel, copper, etc., and the plastic materials may correspond to polycarbonate, ABS, nylon, etc. The material selected generally depends on many factors including but not limited to strength (tensile), density (lightweight), strength to weight ratio, corrosion resistance, formability, finishing, recyclability, tooling costs, and/or the like. The material selected may also depend on electrical conductivity, thermal conductivity, combustibility, toxicity, and/or the like.

In one particular embodiment, the main body 54 including the internal rails 80 is formed from an extruded aluminum tube. Some of the reasons for using aluminum over other materials is that it is light weight and structurally stronger

(e.g., it has very good mechanical properties and strength to weight ratio). This is especially important for hand held devices. Other reasons for using aluminum include: reduced tooling costs (e.g., injection moldings can be cost prohibitive), it is easily formable and extruded in a wide variety of shapes including hollow parts, easily machinable thus making it easy to alter the part after the extrusion process, provides a near net shape, offers superior corrosion resistance, it has high scrap value and is routinely reprocessed to generate new extrusions, and it can be finished using a variety of methods including mechanical and chemical prefinishes, anodic coatings, paints and electroplated finishes.

FIG. 2 is a perspective diagram of a handheld computing device 100, in accordance with one embodiment of the present invention. By way of example, the computing device 100 may generally correspond to the device 50 shown and described in FIG. 1. The computing device 100 is capable of processing data and more particularly media such as audio, video, images, etc. By way of example, the computing device 100 may generally correspond to a music player, game player, video player, camera, cell phone, personal digital assistant (PDA), and/or the like. With regards to being handheld, the computing device 100 can be operated solely by the user's hand(s), i.e., no reference surface such as a desktop is needed. In some cases, the handheld device is sized for placement into a pocket of the user. By being pocket sized, the user does not have to directly carry the device and therefore the device can be taken almost anywhere the user travels (e.g., the user is not limited by carrying a large, bulky and heavy device). In the illustrated embodiment, the computing device 100 is a pocket sized hand held music player that allows a user to store a large collection of music. By way of example, the music player may correspond to the iPod series MP3 players, and more particularly the iPod mini manufactured by Apple Computer of Cupertino, Calif.

As shown, the computing device 100 includes a housing 102 that encloses and supports internally various electrical components (including integrated circuit chips and other circuitry) to provide computing operations for the device. The integrated circuit chips and other circuitry may include a microprocessor, hard drive, Read-Only Memory (ROM), Random-Access Memory (RAM), a battery, a circuit board, and various input/output (I/O) support circuitry. In addition to the above, the housing 102 may also define the shape or form of the device 100. In this particular embodiment, the housing 102 extends longitudinally and has a pill like cross section. The size and shape of the housing 102 is preferably dimensioned to fit comfortably within a user's hand. In one particular embodiment, the housing is formed from an extruded material such as aluminum thereby providing a seamless look along the length of the device 100. That is, unlike conventional housings, the housing 102, particularly the main body, does not include any breaks between the top and bottom ends thereby making it stronger and more aesthetically pleasing.

The computing device 100 also includes a display screen 104. The display screen 104, which is assembled within the housing 102 and which is visible through an opening 106 in the housing 102, is used to display a graphical user interface (GUI) as well as other information to the user (e.g., text, objects, graphics). By way of example, the display screen 104 may be a liquid crystal display (LCD). In some cases, the housing 102 may include a window, which is positioned in the opening in front of the display in order to protect the display from damage. The window is typically formed from a clear material such as clear polycarbonate plastic.

The computing device 100 also includes one or more input devices 108 configured to transfer data from the outside world

into the computing device 100. The input devices 108 may for example be used to perform tracking/scrolling, to make selections or to issue commands in the computing device 100. By way of example, the input devices 108 may correspond to keypads, joysticks, touch screens, touch pads, track balls, wheels, buttons, switches, and/or the like. In the illustrated embodiment, the computing device 100 includes a touch pad 108A and one or more buttons 108B, which are assembled within the housing 102 and which are accessible through a second opening 110 in the housing 102.

The touch pad 108A generally consists of a touchable outer surface 111 for receiving a finger for manipulation on the touch pad 108A. Although not shown, beneath the touchable outer surface 111 is a sensor arrangement. The sensor arrangement includes a plurality of sensors that are configured to activate as the finger passes over them. In the simplest case, an electrical signal is produced each time the finger passes a sensor. The number of signals in a given time frame may indicate location, direction, speed and acceleration of the finger on the touch pad, i.e., the more signals, the more the user moved his or her finger. In most cases, the signals are monitored by an electronic interface that converts the number, combination and frequency of the signals into location, direction, speed and acceleration information. This information may then be used by the device 100 to perform the desired control function on the display screen 104.

The position of the touch pad 108A relative to the housing 102 may be widely varied. For example, the touch pad 108A may be placed at any external surface (e.g., top, side, front, or back) of the housing 102 that is accessible to a user during manipulation of the device 100. In most cases, the touch sensitive surface 111 of the touch pad 108A is completely exposed to the user. In the illustrated embodiment, the touch pad 108A is located in a lower, front area of the housing 102. Furthermore, the touch pad 108A may be recessed below, level with, or extend above the surface of the housing 102. In the illustrated embodiment, the touch sensitive surface 111 of the touch pad 108A is substantially flush with the external surface of the housing 102.

The shape of the touch pad 108A may also be widely varied. For example, the touch pad 108A may be circular, rectangular, square, oval, triangular, and the like. In the illustrated embodiment, the touch pad 108A is circular. Circular touch pads allow a user to continuously swirl a finger in a free manner, i.e., the finger can be rotated through 360 degrees of rotation without stopping. Furthermore, the user can rotate his or her finger tangentially from all sides thus giving it more range of finger positions. For example, when the device 100 is being held, a left handed user may choose to use one portion of the touch pad 108A while a right handed user may choose to use another portion of the touch pad 108A. More particularly, the touch pad is annular, i.e., shaped like or forming a ring. When annular, the inner and outer perimeter of the shaped touch pad defines the working boundary of the touch pad.

The buttons 108B are configured to provide one or more dedicated control functions for making selections or issuing commands associated with operating the device 100. By way of example, in the case of a music player, the button functions may be associated with opening a menu, playing a song, fast forwarding a song, seeking through a menu and the like. In most cases, the button functions are implemented via a mechanical clicking action although they may also be associated with touch sensing similar to the touch pad 108A. The position of the buttons 108B relative to the touch pad 108A may be widely varied. For example, they may be next to one another (center or peripheral), spaced apart or integrated into

11

a single unit. Several touch pad/button arrangements, which may be used in the device **100**, are described in greater detail in pending patent application Ser. Nos.: 10/643,256, 10/188,182, 10/722,948, which are all herein incorporated by reference.

The computing device **100** also includes one or more switches **112** including power switches, hold switches, and the like. The power switch is configured to turn the device **100** on and off, and the hold switch is configured to activate or deactivate the touch pad **108A** and/or buttons **108B**. This is generally done to prevent unwanted commands by the touch pad **108A** and/or buttons **108B**, as for example, when the device **100** is stored inside a user's pocket. Like the touch pad **108A** and buttons **108B**, the switches **112** are accessible through a third opening **114** in the housing **102**.

The device **100** may also include one or more connectors **116** for transferring data and/or power to and from the device **100**. In the illustrated embodiment, the device **100** includes an audio jack **116A**, a data port **116B** and a power port **116C**. The audio jack **116A** allows audio information to be outputted from the device **100**. The data port **116B** allows data to be transmitted and received to and from a host device such as a general purpose computer (e.g., desktop computer, portable computer). The data port **116B** may be used to upload or download audio, video and other image data to and from the device **100**. For example, the data port **116B** may be used to download songs and play lists, audio books, ebooks, photos, and the like into the storage mechanism of the computing device **100**. The power port **116C**, on the other hand, allows power to be delivered to the computing device **100**. In some cases, the data port **116B** may serve as both a data and power port thus replacing a dedicated power port **116C**. A data port such as this is described in greater detail in pending U.S. patent application Ser. No. 10/423,490, which is herein incorporated by reference.

FIGS. **3A** and **3B** are diagrams of a hand held computing device **150**, in accordance with one embodiment of the present invention. FIG. **3A** is perspective diagram showing the computing device **150** in its assembled form, while FIG. **3B** is an exploded perspective diagram showing the computing device **150** in its unassembled form. The computing device **150** may generally correspond to the computing device **100** shown and described in FIG. **2**.

The computing device **150** includes a housing **152**, which serves to support the internal components of the computing device **150** in their assembled position within the device **150**. The housing **152** includes several components including a seamless enclosure **154**, a bottom end cap **156** and a top end cap **158**. The seamless enclosure **154** extends along a longitudinal axis **160**, and includes an internal lumen **162** which is sized and dimensioned for receipt of the internal components of the computing device **150** through a first open end **164** and a second open end **166** opposite the first open end **164**. The end caps **156** and **158** cover the open ends **164** and **166** of the seamless enclosure **154** in order to provide a fully contained housing **152**. Although the end caps **156** and **158** can be applied in a variety of ways, in this particular embodiment, each of the end caps **156** and **158** includes a shape that coincides with the internal shape of the seamless enclosure **154** such that they may be inserted into the open ends, i.e., the outer periphery of the end caps **156**, **158** matches the inner periphery of the lumen **162**. Furthermore, the end caps **156** and **158** are positioned to be flush with the bottom **170** and top surfaces **172** of the seamless enclosure **154** thereby forming a housing **152** with a substantially uniform appearance.

In order to help guide at least a portion of the internal components to their desired position within the seamless

12

enclosure **154**, the seamless enclosure **154** includes an internal rail system **176** including a pair of rails **177** that protrude out the inner sides of the seamless enclosure **154**. The two rails **177**, which are similarly shaped, are placed in an opposed relationship directly across from one another. The rails **177** provide reference surfaces for receiving and supporting some portion of the internal components. The portion of the internal components that engages the rails **177** is typically an edge of the internal components. The internal rail system **176** is integrally formed with the seamless enclosure **154**. By integral, it is meant that the seamless enclosure **154** and the rail system **176** are formed from a single piece of material.

In fact, the seamless enclosure **154** along with integrally formed internal rails **176** are preferably formed from an extrusion process. The extrusion process produces the desired cross section in a continuous tube, which can be cut to form a seamless enclosure **154** including the internal rails **176** with a desired length. That is, the seamless enclosure **154** including the internal rails **176** is formed from an elongated continuous extruded tube that has been cut to a desired length. As should be appreciated, the features of the internal rail **176** are extruded along with the seamless enclosure **154** thereby forming rails that have the same length as the seamless enclosure, i.e., the extrusion process produces rails that extend from the top to the bottom end of the seamless enclosure.

Although the extrusion process allows for a variety of materials, in this particular embodiment, the continuous tube is formed from a metal material and more particularly from aluminum (or some other material that has similar properties to aluminum). The end caps **156** and **158**, on the other hand, are formed from a plastic material such as ABS using a manufacturing process such as injection molding.

Moving along, the internal components of the computing device **150** include a printed circuit board **180** that contains various integrated circuit chips and other circuitry that provide computing operations for the computing device **150**. The printed circuit board **180** may for example include a microprocessor **182**, memory **184**, a data port **186**, and a switch **188**. Although not shown, the printed circuit board **180** may also contain interconnecting circuitry and related components that help to operatively couple the various internal components together. In order to provide access to some of these components, the top end cap **158** includes an opening **189A** for the switch **188** and the bottom end cap **156** includes an opening **189B** for the data port **186**. As shown, the switch **188** may include a switch cap **191** that is snapped onto the switch **188** after the top end cap **158** is finally assembled.

The internal components of the computing device **150** also include a display **190** such as for example a liquid crystal display. The liquid crystal display **190** is mounted on the front of the printed circuit board **180**. The LCD **190** may be mounted to the PCB **180** using a variety of techniques. By way of example, the LCD **190** may include locking tabs that snap onto the printed circuit board **180** in order to secure the LCD **190** thereto. Alternatively, the LCD **190** may be a stand alone assembly, i.e., floating rather than mounted to the PCB **180**. In either case, the LCD **190** is operatively coupled to the printed circuit board **180** and its various components. This may for example be accomplished through a flex circuit connector that couples to a connector located on the printed circuit board **180**.

In order to provide visible access to the display **190**, the seamless enclosure **154** includes an access opening **192** having a shape that coincides with the shape of the viewing area of the LCD **190**. The access opening **192** may be formed by processes such as machining, drilling, cutting, punching and/

13

or the like. In most cases, a clear window **194** (typically formed from plastic) is positioned in the access opening **192** in front of the LCD **190** in order to protect the LCD **190** from damage. In fact, when assembled, the window **194** may be considered a portion of the housing **152**. The window **194** may be attached to the seamless enclosure **154** using a variety of techniques including but not limited to fasteners, snaps, adhesives, etc. In the illustrated embodiment, the window **194** includes a raised section **196** that sits in the opening **192** and that is either substantially flush or recessed with the outer surface of the seamless enclosure **154** so that it does not protrude above the outer surface and a flange section **198** having an adhesive layer that secures the window **194** to the inner surface of the seamless enclosure **154**. By having the window flush or recessed, scratching of the window is substantially avoided.

The internal components of the computing device **150** also include a hard drive **200**. The hard drive **200**, which is located at the rear of the printed circuit board **180**, is operatively coupled to the printed circuit board **180** and its various components. This may for example be accomplished through a flex circuit connector that couples to a connector located on the printed circuit board **180**. The hard drive **200** may be mounted (as shown) or it may be free floating relative to the PCB **180**. Although not a requirement, the hard drive **200** may be surrounded by a plurality of bumpers **202** that serve to protect the hard drive **200** when assembled, i.e., the bumpers **202** help to prevent shocks to the hard drive **200**. They also may provide a surface that helps retain the hard drive **200** within the housing **152** (e.g., friction, compliance, etc.). As should be appreciated, the hard drive gives the device massive storage capacity unlike flash based devices. By way of example, the hard drive may have capacities of 5 GB, 10 GB, 15 GB, 20 GB and so on. To cite an example, when the device is used as a music player, a 20 GB hard drive can store up to 4000 songs or about 266 hours of music.

The internal components of the computing device **150** also include a battery **206**. The battery **206**, which is located at the rear of the printed circuit board **180**, is operatively coupled to the printed circuit board **180** and its various components. This may for example be accomplished through a connector that couples to a connector located on the printed circuit board **180**. In some cases, the battery may be attached to the backside of the PCB using for example an adhesive such as double sided tape. In other cases, the battery **206** may be free floating. By way of example, the battery may correspond to a rechargeable lithium polymer battery or a lithium ion prismatic cell. These types of batteries are capable of offering about 10 hours of continuous playtime to the device **150**.

The internal components of the computing device **150** also include an audio subassembly **210**. The audio subassembly **210**, which is located at the top of the printed circuit board **180**, is operatively coupled to the printed circuit board **180** and its various components. The audio subassembly **210** includes at least a small printed circuit board **212** and an audio jack **214**. The audio subassembly may also contain various circuit components and interconnecting circuitry, which are attached to the PCB **212**. Although the audio subassembly may be free floating, in the illustrated embodiment, the audio subassembly **210** is mechanically coupled to the PCB **180** so that the PCB **180** and audio subassembly **210** operate as a single unit (i.e., form a single structure). By way of example, they may be coupled together using fasteners, adhesives or snaps.

In one particular embodiment, the audio subassembly **210** is both operatively and mechanically coupled to the main printed circuit board **180** and its various components through

14

a connector, which is located on the audio printed circuit board **212**, and which couples to a connector located on the main printed circuit board **180**. The coupling between the connectors may include a friction element or mechanical detent that substantially secures the audio subassembly **210** to the printed circuit board **180**. In order to provide access to the audio jack **214** audio subassembly **210**, the top end cap **158** includes an opening **193** having a shape that coincides with the shape of the audio jack **214**. In most cases, the housing of the audio jack **214** is substantially flush with the outer surface of the top end cap **158**.

During assembly and referring to the top end of the seamless enclosure **154**, the integrated system comprising, the PCB **180**, LCD **190**, hard drive **200**, battery **206** and audio subassembly **210** is inserted into the lumen **156** of the seamless enclosure **154** as a single unit. The printed circuit board **180** essentially acts as a carrier for placing these components inside the housing **152**. During assembly, the PCB **180** is inserted in the direction of the y axis into the space provided by a portion of the side and bottom surfaces of the seamless enclosure **154** as well as the bottom surface of the internal rail system **176**. This space may be referred to as a channel. During insertion, a top surface of the PCB **180** slides along the bottom surface of the internal rail system **176** within the space. As should be appreciated, the side walls, bottom surface and rails help constrain the PCB **180** within the housing **152** during and after insertion. The PCB **180** is typically slid into the seamless enclosure **154** to a depth (y) that places the LCD **190** directly behind the access opening **192**. Furthermore, the internal rail system **176** helps locate the PCB **180** and thus the LCD **190** in the direction of the z axis while the side walls of the seamless enclosure **154** help locate the PCB **180** and thus the LCD **190** in the direction of the x axis.

In order to ensure proper positioning as well as to help secure the integrated system in place, a top plate **218** may be provided that prevents further sliding and sets the final position of the integrated system. The top plate **218** may be attached to the main PCB **180** or the PCB **212** of the audio subassembly **210**. The top plate **218** may be attached using a variety of techniques including but not limited to fasteners, adhesives, snaps and/or the like. In the illustrated embodiment, the top plate **218** is attached to the PCB **212** of the audio subassembly **210**. When the integrated system is slid into the lumen **162**, the bottom surface of the top plate **218** abuts a recessed area **220** formed in the top surface of the seamless enclosure **154**. The recessed area **220** may for example be formed by machining a portion of the top surface of the seamless enclosure **154** (including the rails **177**). Once positioned against the recessed area **220**, the top plate **218** is attached to the seamless enclosure **154** using fasteners such as screws **219**.

The depth of the top plate **218** generally depends on the desired position of the top end cap **158**. In order to produce a flush top surface, the top plate **218** is typically positioned to a depth corresponding to the thickness of the top plate **218** and the top end cap **158**. Once the top plate **218** is secured, the top end cap **158** may be attached thereto. The top end cap **158** may be attached to the top plate **218** using fasteners, snaps, adhesives, and/or the like. In order to make assembly easier and to prevent the undesirable look of fasteners, the top plate **218** may include several retaining features for receiving tabs located on the inside surface of the top end cap **158**. When the top end cap **158** engages the top plate **218**, the tabs are inserted into the retaining features thereby securing the top end cap **158** to the top plate **218** (via a snapping action).

In one embodiment, the audio subassembly **210** includes a positioning adjustment portion (not shown) configured to

15

provide position relief when attaching the top plate **218** to the seamless enclosure **154**. That is, the adjustment portion allows some degree of tolerance or play so that the top plate **218**, which is connected to the integrated system via the audio subassembly **210**, can be precisely placed relative to the seamless enclosure **154**. The adjustment portion may be separate component or be integrally formed with the PCB **212**. When separate, the adjustment portion may be or include a compliant member, a flexure, a mechanical mechanism and/or the like. When integral, the adjustment portion may be a flexure formed from the PCB **212**. In particular, the adjustment portion may be a tab that has been partially cut away from the PCB **212** thereby enabling it to flex or bend.

The internal components of the computing device **150** also include an input assembly **230**. The input assembly **230** may be widely varied. The input assembly generally depends on the type of device. In the illustrated embodiment, the input assembly **230** includes a touch pad **232** and a center switch **234** positioned on a frame **236**. The switch **234** is a portion of a button, which may be actuated by a user to perform actions in the device **150**. Although the input device **230** is structurally separated from the printed circuit board **180**, it is operatively coupled to the printed circuit board **180** and its various components. This may be accomplished for example through a flex circuit connector that couples to a connector located on the printed circuit board **180**. This connection is typically made after the PCB **180** and input device **230** have been inserted into the seamless enclosure **154**.

In some cases, the touch pad **232** is capable of moving relative to the frame **236** in order to actuate additional mechanical switches housed within the frame **236**. Each of the switches represents a button, which may be actuated by a user. By way of example, the input assembly **230** may correspond to any of those input devices disclosed in U.S. patent application Ser. No. 10/643,256, which is herein incorporated by reference.

In order to provide user access to the input assembly **230**, the seamless enclosure **154** includes an access opening **237** having a shape that coincides with the shape of the touch pad **232**. Like the first access opening **192**, the second access opening **237** may be formed from processes (individually or in combination) such as machining, drilling, cutting, punching and/or the like. In most cases, a button cap **238** and cover **239** is positioned in the access opening **237** in front of the touch pad **232** and switch **234** in order to seal the device **150** and protect the touch pad **232** and switch **234** from damage. The cover **239** is generally sized for placement in the access opening **237** and to provide a surface that is substantially flush with the outer surface of the seamless enclosure **154**. The cover **239** is typically attached to the touch pad **232** using an adhesive. The button cap **238** typically includes a flange portion that is trapped between the cover **239** and the input assembly **230** thereby securing the button cap **238** to the input assembly **230**.

During assembly and referring to the bottom end of the seamless enclosure **154**, the input assembly **230** is inserted into the lumen **156** of the seamless enclosure **154**. The frame **236** acts as a carrier for placing the input assembly **230** inside the housing **152**. During assembly, the input assembly **230** is inserted in the direction of the y axis into the space provided by a portion of the side and top surfaces of the seamless enclosure **154** as well as the top surface of the internal rail system **176**. This space may be referred to as a channel. During insertion, a bottom surface of the frame **236** slides along the top surface of the internal rail system **176** within the space. As should be appreciated, the side walls, top surface and rails help constrain the input assembly **230** within the

16

housing **152** during and after insertion. The input assembly **230** is typically slid into the seamless enclosure **154** to a depth (y) that places the touch pad **232** directly behind the access opening **237**. The depth may be set by posts located inside the seamless enclosure. In the illustrated embodiment, the window **193** includes a pair of abutment stops **240** that prevents further sliding and sets the final position of the input assembly **230** in the y direction. Furthermore, the internal rail system **176** helps locate the touch pad **232** and switch **234** in the direction of the z axis while the side walls of the seamless enclosure **154** help locate the touch pad **232** and switch **234** in the direction of the x axis.

In order to ensure proper positioning as well as to help secure the input assembly **230** in place, the input assembly **230** may include a locking feature that locks the input assembly **230** in place when the input assembly **230** is finally inserted into the seamless enclosure. In one embodiment, the locking feature is in the form of a tab **242** that snaps into a recess located on the inner surface of the seamless enclosure **154**. The recess may be formed by machining a groove in the inner surface of the seamless enclosure **154** at a position that coincides with the input assembly **230** when it is finally inserted.

Like the top end, the bottom end may include a structural plate, i.e., bottom plate **244**. The bottom plate **244** is configured to act as a reference support surface for the bottom end cap **156**. It may also act as a reference surface for the input assembly **230** or the main system assembly. The bottom plate **244** may be connected to the seamless enclosure **154** and/or the input assembly **230**. The bottom plate **244** may be attached using a variety of techniques including but not limited to fasteners, adhesives, snaps and/or the like. By way of example, the bottom plate **244** may be connected in a manner similar to the top plate (attached to the input assembly and inserted into a recess).

Alternatively, as shown in the Figure, the bottom plate **244** may include retaining features **246** that snap into recesses formed in the inner surface of the seamless enclosure **154** thereby mechanically securing the bottom plate **244** to the seamless enclosure **154**. The recesses may be formed by machining grooves in the inner surface of the seamless enclosure **154** at a position that coincides with the retaining features **246** when the bottom plate **244** is inserted in the seamless enclosure **154**. During assembly, the retaining features **246** are flexed inwardly, and the bottom plate **244** is placed inside the seamless enclosure **154**. Once the bottom plate **244** is correctly positioned next to the recesses, the retaining features **246** are unflexed outwardly thereby causing them to be outwardly extended into the recesses, i.e., the retaining features **246** are received by the recesses. A tool may be required to flex the retaining features in a manner analogous to retaining rings. Unlike retaining rings, however, the bottom plate is not circular, and spans the inside of the enclosure to support internal and external parts. Furthermore, the bottom plate is fixed in place and cannot rotate as circular retaining rings thus providing a reference surface in more than just the y direction, i.e., the bottom plate provides a reference surface in the x, y and z directions. This enables the bottom plate to fixedly support the end cap.

The depth of the bottom plate **244** generally depends on the desired position of the bottom end cap **156**. In order to produce a flush bottom surface, the bottom plate **244** is typically positioned to a depth corresponding to the thickness of the bottom plate **244** and the bottom end cap **156**. Once the bottom plate **244** is secured, the bottom end cap **156** may be attached thereto. The bottom end cap **156** may be attached to the bottom plate using fasteners, snaps, adhesives, and/or the

17

like. In order to make assembly easier and to prevent the undesirable look of fasteners, the bottom plate **244** may include several retaining features for receiving tabs located on the inside surface of the bottom end cap **156**. When the bottom end cap **156** engages the bottom plate **244**, the tabs are inserted into the retaining features thereby securing the bottom end cap **156** to the bottom plate (via a snapping action).

The bottom plate may be formed from a variety of materials such as metals and plastics. The material that is selected typically offers a balance between resistance to deformation so as to provide a structural surface and bendability so that the flexure arms can be flexed during installation. In the illustrated embodiment, the bottom plate is formed from stainless steel, and more particularly high hardness stainless steel.

FIG. 4, which is top view, in cross section of the assembled device **150**, shows the position of the various components of the integrated system inside the housing **152** and more particularly the seamless enclosure **154**. As shown, the top surface at the edge of the printed circuit board **180** abuts the bottom surface of the rails **177**. Furthermore, the battery **206** and hard drive **202** are contained within the lower channel formed by the rails, sides and back surface of the seamless enclosure **154**. In most cases, there is a snug fit between these components and the surrounding portions of the seamless enclosure **154** so as to help hold the integrated system in place. Moreover, the LCD **190** protrudes above the rails **177** through a gap formed between the rails **177** so that it is positioned directly underneath the window **194**. In some cases, the gap may be dimensioned to form a snug fit between the LCD and rails to better align the LCD with the opening, i.e., the rails provide a reference surface for the LCD in the x direction.

FIG. 5, which is bottom view, in cross section of the assembled device **150**, shows the position of the input assembly **230** inside the housing **152**, and more particularly the seamless enclosure **154**. As shown, the bottom surface at the edge of the frame **236** abuts the top surface of the rails **177**. Furthermore, most of the input assembly **230** is contained within the upper channel formed by the rails, sides and surface of the seamless enclosure **154**. In most cases, the input assembly **230** is sized and dimensioned to fit snugly inside the upper channel. A small portion of the frame (or other component of the input assembly **230**) may be positioned within the gap formed between the two rails **177**.

FIGS. 6A-6C show the insertion and mounting of the input assembly **230** inside the seamless enclosure **154**. As shown in FIGS. 6A and 6B, the input assembly **230** is inserted into the bottom end of the seamless enclosure **154**. In particular, the front edge of the input assembly **230** is placed within the upper channel against the rails **177**, and the input assembly **230** is slid along the rails **177** into the seamless enclosure **154**. As shown in FIG. 6C, when the input assembly **230** nears its final position in the y direction, the tab **242** on the rear of the input assembly **230** snaps into a recess **256** located on the inner top surface of the seamless enclosure **154** thereby securing the input assembly **230** between this point and the abutment stops **240** located on the window **194**. The positions of the abutment stop **240** and recess **256** are preferably positioned such that the tab **242** engages the recess **256** as the input assembly **230** presses against the abutment stop **240**. This particular arrangement helps prevent any subsequent movement of the input assembly **230**, i.e., locks it into place (in the y direction).

FIGS. 7A and 7B show the bottom plate **244** in its unassembled and assembled positions. The bottom plate **244** includes a body **261** and a plurality of flexure arms **246**. The body **261** is typically configured to fill the available space

18

between the opposing sets of retaining arms **256** so as to produce a more rigid structure for supporting the various components enclosed within or attached to the enclosure **154**. The flexure arms **246**, which extend from the body **261**, are configured to bend in towards the body **261** when a force **F** is applied to the flexure arms **246**. In some cases, the interface between the body and the flexure arms includes a radius. The radius may be adjusted to tune the stiffness of the flexure arms. The force **F** may for example be provided by a pinching tool that engages holes **262** located in each of the flexure arms **246**.

Both the body and the arms are configured to cooperate to form the shape of the bottom plate. The shape may be widely varied although the shape is generally configured to be non circular so as to provide a better reference surface (e.g., substantially rectangular). In fact, the shape may coincide with the shape of the lumen found in the enclosure.

The bottom plate **244** may be formed from a variety of structural materials including metals and plastics. By way of example, the bottom plate **244** may be formed from stamping a sheet of metal (e.g., steel) or from molding a piece of plastic.

As shown in FIG. 7B, the bottom plate **244** is positioned inside the lumen **162** of the seamless enclosure **154**. In particular, the flexure arms **246** are retained within slots **263** located on the inside surface of the seamless enclosure **154**. In fact, the flexure arms may include outward protrusions that provide a better interface between the flexure arms and the slots. The bottom plate **244**, which is designed to receive the bottom end cap **156**, is positioned at the end of the seamless enclosure **154** so as to produce a reference support surface for the bottom end cap **156**. In essence, the bottom plate **244** when retained acts as an extension of the seamless enclosure **154**. The depth of the bottom plate **244** is typically configured to place the outer surface of the bottom end cap **244** substantially flush with the bottom surface **264** of the seamless enclosure **154**. The bottom plate **244** may include various features **266** for receiving locking tabs located on the bottom end cap **156**. As should be appreciated, the features may be openings or voids that receive snaps on the bottom of the end cap, i.e., the snaps snap into the openings thereby securing the bottom end cap to the bottom plate. The bottom plate **244** may also include an opening **267**, which provides a clearance for the connector **186**.

FIG. 8 is a diagram of the audio subassembly **210**, in accordance with one embodiment of the present invention. As shown in FIG. 8A, the PCB **212** is divided into a flexure portion **270**, a first base portion **272** and a second base portion **274**. This may be accomplished by cutting a groove in the PCB **212**. The audio jack **214** is attached to the first base portion **272** and the top plate **218** is attached to the audio jack **214**. The second base portion **274** includes a connector **276** that mates with a connector on the main PCB **180** in order to operatively and mechanically couple the audio subassembly **210** to the main PCB **180**, i.e., form a single unit. The flexure portion **270** is positioned between the first and second base portions **272** and **274**. The flexure portion **270** allows the first base portion **272** to move relative to the second base portion **274**. The flexure **270** causes the first base portion **272** and thus the top plate **218** to float relative to the main PCB **180** while still being constrained thereto. As shown in FIGS. 8B and 8C, the flexure portion **270** is capable of flexing or bending so that the first base portion **272** can shift relative to the second base portion **274** thereby allowing the top plate **218** to be correctly aligned with the recess **220** of the seamless enclosure **154**. That is, the flexure **270** allows the top plate **218** to shift into mating engagement with the recess **220** of the seamless enclosure.

19

sure 154 thereby producing a tight fit between the top plate 218 and the seamless enclosure 154.

FIGS. 9A-9H are various diagrams of the seamless enclosure 154. As shown, the seamless enclosure 154 includes a planar front surface 280, a back planar surface 282 and rounded sides 284. The access openings 192 and 237 for the LCD 190 and input assembly 230 are located in the front planar surface 280. The seamless enclosure 154 also includes a lumen 162 therethrough that defines openings at each of the ends of the seamless enclosure 154. The rails 177, which extend substantially through the lumen 162, are located in an opposed relationship inside the lumen 162. The rails 177 protrude away from the sides of the lumen 162 and are positioned closer to the front planar surface 280 than the back planar surface 282. The end at the top of the seamless enclosure 154 includes a recess 220 for receiving the top plate 218 and top end cap 158. The recess 220 essentially forms a lip to which the top plate 218 is secured. The end at the bottom of the seamless enclosure 154 includes a cut out section 290 for receiving the bottom plate 244 and the bottom end cap 156. The cut out 290 is formed by shortening the ends of the rails 177. This end also includes a plurality of slots 263 for receiving the flexure arms 246 of the bottom plate 244.

FIG. 10 is a method of manufacturing an electronic device 340, in accordance with one embodiment of the present invention. The electronic device may generally correspond to any of those previously described. The method generally includes several operations including: the formation of the housing 342, the assembly of the internal components including the main system assembly 244 and the touch pad assembly 346, and the final assembly of the housing 348.

Referring first to the formation of the housing 342, the operation starts with block 352 where a tube having internal rails is extruded. Following block 352, the operation proceeds to block 354 where the extruded tube is cut to a desired length. Following block 354, the operation proceeds to block 356 where the access openings are formed in the extruded tube. By way of example, the access opening may be associated with a user interface of the electronic device. Following block 356, the operation proceeds to block 358 where a recess is formed into a top surface of the extruded tube. Following block 358, the operation proceeds to block 360 where one or more threads are formed in the recess at the top surface of the extruded tube. Following block 360, the operation proceeds to block 362 where a portion of the internal rails are removed from the bottom surface of the extruded tube. Following block 362, the operation proceeds to block 364 where slots are formed in the area where the internal rails were removed.

Referring to the assembly of the various components inside the tube 344, the operation starts with block 366 where a window is mounted in one of the access openings. This may for example be accomplished using an adhesive such as glue or tape. Following block 366, the operation proceeds to block 368 where a main system assembly is inserted into the top end of the extruded tube along the lower surface of the internal rails. The main system assembly is typically sized and dimensioned for sliding receipt between the lower surface of the internal rails and the side and back surface of the extruded tube. The main system assembly generally includes a printed circuit board, which acts as the carrier for several components including: system electronics (e.g., microprocessor and memory); an LCD; a battery; I/O assemblies (audio assembly, data port assembly); etc. Following block 368, the operation proceeds to block 370 where the main system assembly is mounted to the extruded tube. This is generally accomplished through a top plate that is attached to the main system assembly. When the main system assembly is finally inserted into

20

the extruded tube, the top plate presses against the upper surface of the recess thereby setting the position of the main system assembly in its desired position along the longitudinal axis of the extruded tube. The top plate is then attached to the extruded tube via screws and the previously formed threads.

Referring to the assembly of the touch pad assembly 346, the operation starts with block 372 where the touch pad assembly is inserted into the bottom end of the extruded tube along the upper surface of the internal rails. The touch pad assembly is typically sized and dimensioned for sliding receipt between the upper surface of the rail and the side and front wall of the extruded tube. When the touch pad assembly is finally inserted into the extruded tube, the top surface of the touch pad assembly presses against a pair of abutment stops located at the bottom end of the window thereby setting the position of the touch pad assembly in its desired position along the longitudinal axis of the extruded tube. In particular, the touch pad of the touch pad assembly is positioned directly behind the second access opening.

Following block 372, the method proceeds to block 374 where the touch pad assembly is operatively coupled to the main system assembly. By way of example, a simple connector connection may be made or a solder connection can be made. In the illustrated embodiment, the touch pad assembly includes a flex connector that couples to a connector located on the PCB. Following block 374, the operation proceeds to block 376 where a button cap and label is situated over the touch pad of the touch pad assembly. The button cap is disposed over a center switch and the label is disposed over an edge of the button cap as well as the touch pad. The label is typically attached to the touch pad using an adhesive. In most cases, the label is positioned in the recessed area formed by the touch pad and the edge of the access opening. The label therefore helps to secure the touch pad assembly in its desired position within the extruded tube. Although not a requirement, the top surface of the label is typically positioned substantially flush with the outer surface of the extruded tube.

Referring to the final assembly of the device, the operation starts with block 378 where the snap plate is inserted into the slotted bottom end of the extruded tube thereby securing the snap plate to the extruded tube. Following block 378, the operation proceeds to block 380 where the bottom end cap is mounted to the bottom end of the extruded tube. This is generally accomplished by positioning the bottom end cap in the recessed area formed by the snap plate and the inner surface of the extruded tube, and snapping tabs located on the bottom end cap into the snap plate thereby securing the bottom end cap to the snap plate. In most cases, the outer surface of the bottom end cap is made flush with the bottom surface of the extruded tube. Following block 380, the operation proceeds to block 382 where the top end cap is mounted to the top end of the extruded tube. This is generally accomplished by positioning the top end cap in the recessed area formed by the top plate and the inner surface of the extruded tube, and snapping tabs located on the top end cap into the top plate thereby securing the top end cap to the top plate. It should be pointed out that during insertion of the top end cap into the recessed area, a protruding member of the audio assembly is inserted through an opening in the top end cap. Because the audio assembly includes a flexure, the protruding member has a small amount of tolerance or play that allows for easy placement through the opening. Once the top end cap is attached, the switch cap may be placed on the switch assembly through another opening in the top end cap.

While this invention has been described in terms of several preferred embodiments, there are alterations, permutations, and equivalents, which fall within the scope of this invention.

21

For example, although the invention is primarily directed at an integrally formed internal rail system, in some cases the internal rail system may be a separate component that is attached within the main body. It should also be noted that there are many alternative ways of implementing the methods and apparatuses of the present invention. For example, although an extrusion process is preferred method of manufacturing the integral tube, it should be noted that this is not a limitation and that other manufacturing methods may be used (e.g., injection molding). It is therefore intended that the following appended claims be interpreted as including all such alterations, permutations, and equivalents as fall within the true spirit and scope of the present invention.

What is claimed is:

1. A handheld music player, comprising:

an elongated extruded tube extending along a longitudinal axis, and having a first open end and a second open end opposite the first open end, the elongated extruded tube defining an internal lumen which is sized and dimensioned for slidable receipt of operational components of the handheld music player, the lumen including rails and a securing mechanism for guiding the operational components to their desired position within the lumen, wherein the securing mechanism comprises a lumen locking feature configured to engage with a locking feature of an operational component to secure the operational component to the tube when the operational component is in its desired position within the lumen.

2. The handheld music player as recited in claim 1, wherein the rails define an upper channel and a lower channel inside the lumen, the upper channel receiving a first operational component, the lower channel receiving a second operational component, the first and second operational components being located relative to a front wall of the elongated extruded tube via the rails.

3. The handheld music player as recited in claim 1, wherein the operational components include at least a memory component that stores a large collection of music and a processing component that plays the music stored in the memory component.

4. The handheld music player as recited in claim 1, wherein the rails include a pair of rails that are placed in a opposed relationship and protrude from opposite sides of the lumen, the pair of rails being integrally formed with the elongated extruded tube, and wherein the elongated extruded tube defines a front wall, side walls and back wall of the handheld music player, the front wall including a first access opening and a second access opening, the handheld music player further including:

a main control assembly containing a microprocessor, display, memory unit, battery connected to a printed circuit board, wherein the main control assembly is disposed in a space provided by the side walls and back wall of the extruded tube and the bottom surface of the pair of rails, the main control assembly being positioned along the longitudinal axis at a location that places the display directly behind the first access opening, the printed circuit board of the main control assembly abutting the bottom surface of the rails thereby locating the display in the direction of the front wall;

an input assembly containing a touch pad and a button positioned on a frame, wherein the input assembly is disposed in a space provided by the side walls and top wall of the extruded tube and the top surface of the pair of rails, the input assembly being positioned along the longitudinal axis at a location that places it directly behind the second access opening, the bottom surface of

22

the frame abutting the top surface of the rails, the rails locating the touch pad and button in the direction of the front wall; and

a first end cap inserted at the first open end of the elongated extruded tube, and a top end cap inserted at the second open end of the elongated extruded tube, the first end cap defining a top wall of the handheld music player, the second end cap defining a bottom wall of the handheld music player, the end caps cooperating with the elongated extruded tube to form a fully contained housing of the handheld music player.

5. The handheld music player of claim 1, wherein the lumen locking feature comprises a recess in an inner wall of the tube and the locking feature of the operational component comprises a flexure tab.

6. A handheld computing device, comprising:

an enclosure including an integral housing member that extends along a longitudinal axis and that includes an internal cavity therein, the integral housing member defining at least a front wall, side walls and back wall of the enclosure, the front wall having a substantially planar front surface, the planar front surface being configured to present a user interface sub-system of the handheld computing device through one or more access openings, the integral housing member having at least one open end and a pair of internal rails that extend parallel to the longitudinal axis and that protrude inwardly into the cavity from opposing side walls of the integral housing member, the open end being configured to receive the user interface sub-system therethrough during assembly of the handheld computing device, the internal rails being configured to locate the user interface sub-system in its desired position relative to the planar front surface of the enclosure when the user interface sub-system is positioned inside the cavity of the integral housing member of the enclosure of the handheld computing device, wherein the housing member includes a locking feature configured to engage with a locking feature on the user interface sub-system to secure the user interface sub-system to the housing member when the user interface sub-system is in its desired position inside the cavity.

7. The handheld computing device as recited in claim 6, wherein the integral housing member is formed from an extruded tube having a substantially seamless construction with a substantially uniform cross section along a longitudinal axis of the extruded tube.

8. The handheld computing device as recited in claim 6, wherein the user interface sub-system includes an output device assembly and an input device assembly, the output device assembly being presented through a first access opening of the integral housing member, the input device assembly being presented through a second access opening of the integral housing member.

9. The handheld computing device as recited in claim 6, wherein the locking feature of the housing member comprises a recess in an inner wall of the housing member, and the locking feature of the user interface sub-system comprises a flexure tab.

10. The handheld computing device as recited in claim 6, wherein the locking feature of the housing member comprises a snap on an inner wall of the housing member, and the locking feature of the user interface sub-system comprises a snap configured to engage with the snap on the inner wall of the housing member.

23

11. A handheld music player, comprising:
operational components including at least one user inter-
face element; and
an elongated extruded tube extending along a longitudinal
axis and having a substantially uniform cross section
along the longitudinal axis, the elongated extruded tube
having a first open end, a second open end opposite the
first open end, and at least one access opening provided
on a wall of the elongated extruded tube, the elongated
extruded tube defining an internal lumen which is sized
and dimensioned for slidable receipt of the operational
components, the lumen including rails extending along
the longitudinal axis for guiding the operational compo-
nents to their desired position within the lumen so as to
expose the user interface element through the access
opening, wherein the lumen further includes a lumen
locking feature configured to engage with a locking
feature of an operational component to secure the opera-
tional component to the tube when the operational com-
ponent is in its desired position within the lumen.
12. The handheld music player as recited in claim 11,
wherein the rails have the same length as the elongated
extruded tube.
13. The handheld music player as recited in claim 11,
wherein the rails define an upper channel and a lower channel
inside the lumen, the upper channel receiving a first opera-
tional component, the lower channel receiving a second
operational component, the first and second operational com-
ponents being positioned at respective predetermined loca-
tions with respect to a front wall of the elongated extruded
tube.
14. The handheld music player as recited in claim 11,
wherein the operational components include:
at least one memory component that stores a collection of
music; and
a processing component that plays the music stored in the
memory component.
15. The handheld music player as recited in claim 11,
wherein the elongated extruded tube defines a front wall,
side walls and back wall of the handheld music player,
the front wall including a first access opening and a
second access opening,
wherein the rails are a pair of internal protrusions provided
in opposed sides of the lumen along the respective side
walls of the elongated extruded tube, the internal protru-

24

- sions being integrally formed with the elongated
extruded tube, each rail having a top surface facing an
inner side of the front wall and a bottom surface facing
an inner side of the back wall;
- and wherein the operational components include:
a main control assembly having a printed circuit board,
a microprocessor and a display connected to the
printed circuit board, the main control assembly being
inserted in the lumen such that an upper surface of the
printed circuit board abuts the bottom surface of the
rails, the display provided on the upper surface being
disposed directly under the first access opening; and
an input assembly having an input device and a frame
holding the input device, the input assembly being
inserted in the lumen such that a lower surface of the
frame abuts the top surface of the rails, the input
device being disposed directly under the second
access opening.
16. The handheld music player as recited in claim 15,
wherein the main control assembly further includes a
memory unit and a battery provided on a lower surface of the
printed circuit board.
17. The handheld music player as recited in claim 15,
further comprising:
an audio assembly operatively coupled with the print cir-
cuit board of the main control assembly.
18. The handheld music player as recited in claim 15,
wherein the input device includes a touch pad and a switching
button.
19. The handheld music player as recited in claim 15,
further comprising:
a first end cap provided at the first open end of the elongated
extruded tube, the first end cap defining a top wall of the
handheld music player; and
a top end cap provided at the second open end of the
elongated extruded tube, the second end cap defining a
bottom wall of the handheld music player,
wherein the first and second end caps cooperates with the
elongated extruded tube to form a fully contained hous-
ing of the handheld music player.
20. The handheld music player as recited in claim 11,
wherein the lumen locking feature comprises a recess in an
inner wall of the tube and the locking feature of the opera-
tional component comprises a flexure tab.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,649,744 B2
APPLICATION NO. : 12/395570
DATED : January 19, 2010
INVENTOR(S) : Stephen Paul Zadesky et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page 2, in column 2, under "Other Publications", line 6, delete "cfm?articleID" and insert -- cfm?articleID --, therefor.

Title page 2, in column 2, under "Other Publications", line 6, delete "Downloaded" and insert -- Downloaded --, therefor.

Signed and Sealed this
Eleventh Day of October, 2011

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive, flowing style with a large initial "D" and a stylized "K".

David J. Kappos
Director of the United States Patent and Trademark Office